





QM-ESV: Matte WR frontlit scrim banner

Our signature matte porous coating offers a bright white finish for high density color display. Water and scratch resistant suitable for indoor and short-term outdoor banners. High denier for ultra durability and tear strength.



Benefits:

- Water Resistant
- Smooth Non-Glare Finish
- Tear Resistant

Applications:

- Indoor Banners
- Point of Sale Display
- Short Term Outdoor Banners

| TECHNICAL DATA: QM-ESV — MATTE WR FRONTLIT SCRIM BANNER | | | |
|---|--------------------------|---|--|
| SURFACE FINISH: | Matte | GLOSS MEASUREMENT: | 2 +/- 10% by angle of 60° |
| DENIER: | 500D × 500D | DURABILITY: | Indoor: Up to 1 year Outdoor: Up to 6 months |
| BASE MATERIAL: | PVC | ROLL LENGTH: | 60 FT. |
| BASE WEIGHT: | 490 GSM +/- 10% | ROLL WIDTHS: | 24", 36", 42", 50", & 60" |
| CALIPER: | 15 Mil +/- 1 | CORE: | 2″ |
| BRIGHTNESS: | 101 (ISO Blue Whiteness) | PRINT SIDE: | Print Side Out |
| WHITENESS: | 125 (CIE Ganz) | INK RECOMENDATIONS: | AQUEOUS |
| OPACITY: | 98 | STORAGE: Up to six months if stored in proper conditions (cool, dry place 50-80°) | |



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to six months if stored in proper conditions (cool, dry place 50-80°)