



OM-LAMGL: Gloss pressure sensitive lamination film with liner

General, everyday laminate with "cold" permanent adhesive. 4 mil PVC base works well with almost any media type, unlike heat-assisted laminates.



Benefits:

- Ultra Clear Visibility
- Waterproof
- Protects Graphics
- Professional Smooth Gloss
 Finish

Applications:

Millennium

- Indoor Signage
- High Traffic Advertising
- Short Term Outdoor Signage
- Menus

TECHNICAL DATA: QM-LAMGL – GLOSS PRESSURE SENSITIVE LAMINATION FILM WITH LINER

SURFACE FINISH:	Gloss	FACE STOCK CALIPER:	4 Mil +/- 1
BASE MATERIAL:	PVC	DURABILITY:	Indoor: Up to 1 year Outdoor: Up to 6 months
ADHESIVE MATERIAL:	Permanent Solvent Acrylic	ROLL LENGTH:	150 Ft.
LINER MATERIAL:	Kraft w/PE Coating One Side	ROLL WIDTHS:	38", 43", 51", 54", & 61"
LINER WEIGHT:	80 GSM +/- 10%	CORE:	3″
LINER CALIPER:	4 +/- 1 Mil	PRINT SIDE:	Print Side Out
FACE STOCK WEIGHT:	105 GSM +/- 10%	INK RECOMMENDATIONS:	N/A

STORAGE: Up to six months if stored in proper conditions (cool, dry place 50-80°)



This media is designed for digital printing applications using OEM printers with their accompanyir g OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environm-ntal conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70° F $\pm 5^\circ$ F and relative humidity of 50% RH $\pm 3\%$ RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to six months if stored in proper conditions (cool, dry place 50-80°)