



QM-MAXVUE: Mesh 50/50 view PVC banner w/ removable liner

Our 14 mil mesh banner with liner is reinforced with polyester scrim for added durability. The liner makes the printing process easier by preventing ink spray through and helping the media to feed easily through the printer. 50% hole to substrate ratio allows for vivid images and high volume airflow.



Benefits:

- Fire Retardant
- Perforated To Decrease Wind Resistance
- Durable and Tear Resistant
- Polyester & PVC Composition
- Non Glare Matte Finish



Applications:

- Outdoor Banners
- Window Signage
- Fence Signage
- Job Site Signage
- Hanging Banners

Registered Latex Developer



TECHNICAL DATA: QM-MAXVUE – MESH 50/50 VIEW PVC BANNER W/ REMOVABLE LINER

SURFACE FINISH:	Mesh White Gloss	OPACITY:	50/50
BASE MATERIAL:	PVC/Polyester Fabric	DURABILITY:	Indoor: Up to 1 year Outdoor: 6 months
BASE WEIGHT:	244 GSM +/- 10%	ROLL LENGTH:	150 FT.
CALIPER:	14 Mil +/- 1	ROLL WIDTHS:	38", 54", & 60"
BRIGHTNESS:	81 (ISO Blue Whiteness)	CORE:	3"
WHITENESS:	103 (CIE Ganz)	PRINT SIDE:	Print Side Out
GLOSS MEASUREMENT:	10 +/- 10% by angle of 60°	INK RECOMMENDATIONS:	 ECO-SOLVENT  LATEX  UV



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)