



QM-PPGWR: Professional gloss microporous polypropylene

Our elite polypropylene is our highest performing film banner. It's superior tear resistance with its microporous coating gives it the ability to reproduce photo quality images, while also being a perfect solution for indoor signage. Requires no lamination unless higher protection is needed.



Benefits:

- Water Resistant
- Professional High Gloss Finish
- Tear Resistance
- Increased Durability


Applications:

- POP Display
- Indoor Banners
- Photo Reproduction
- Short Term Outdoor Signage

Registered Latex Developer



TECHNICAL DATA: QM-PPGWR — PROFESSIONAL GLOSS MICROPOROUS POLYPROPYLENE

SURFACE FINISH:	Gloss	GLOSS MEASUREMENT:	34 +/- 10% by angle of 60°
BASE MATERIAL:	Polypropylene	DURABILITY:	Indoor: Up to 1 year Outdoor: 6 months
BASE WEIGHT:	160 GSM +/- 10%	ROLL LENGTH:	100 FT, 200 FT.
CALIPER:	8 mil	ROLL WIDTHS:	36", 42", 50", & 60"
BRIGHTNESS:	95 (ISO Blue Whiteness)	CORE:	2"
WHITENESS:	113 (CIE Ganz)	PRINT SIDE:	Print Side Out
OPACITY:	99	INK RECOMENDATIONS:	 AQUEOUS



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)