



QM-WRPPBO: Hybrid matte blackout stay-flat polypropylene

WRPPBO's smooth matte microporous receptive coating will allow for heavy ink loads and sharp resolution on any aqueous, latex, or uv printing platform. The internal blackout layer keeps your graphics bright with no wash out from lights penetrating your graphic. This is the perfect short term banner stand, trade show display, and poster material.



Benefits:

- Instant Dry Coating
- Water Resistant
- Tear Resistant
- 100% Opaque
- Economical

Applications:

- Banner Stands
- Posters
- Trade Show Display
- Indoor Signage
- Short Term Outdoor Signage

Registered Latex Developer



TECHNICAL DATA: QM-WRPPBO — HYBRID MATTE BLOCKOUT STAY-FLAT POLYPROPYLENE

SURFACE FINISH:	Matte	DURABILITY:	Indoor: 1 year Outdoor: 6 months
BASE MATERIAL:	Hybrid Polypropylene	GLOSS MEASUREMENT:	2 +/- 10% by angle of 60°
BASE WEIGHT:	185 GSM +/- 10%	ROLL LENGTH:	100 FT.
CALIPER (mil):	8 +/- 1	ROLL WIDTHS:	36", 42", & 60"
BRIGHTNESS:	96 (ISO Blue Whiteness)	CORE:	3"
WHITENESS:	125 (CIE Ganz)	PRINT SIDE:	Print Side Out
OPACITY:	100	INK RECOMMENDATIONS:	AQUEOUS UV LATEX



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)