



Magnate

Eco Solvent, Latex, UV Media



QM-TFR: Removable adhesive matte media with ANSI Anti-Slip Certification

Maximize indoor advertising and messaging space by adding graphics to walls and surfaces, carpets and floors. Matte finish fabric with sandpaper-like grit for added anti-slip properties. Bright white coating for superior printing and crisp graphics. Tear resistant material makes it easy to remove. Paper liner for easy contour cutting, printing, and application. Customize your interior floor and wall graphics to stand out from others!



Benefits:

- Easy to Apply
- Water Resistant
- Durable / Tear Resistant
- Slip Resistant

Applications:

- Walls
- Carpet
- Floors
- Indoor Surfaces



Registered Latex Developer



TECHNICAL DATA: QM-TFR - REMOVABLE ADHESIVE MATTE MEDIA WITH ANSI ANTI-SLIP CERTIFICATION

SURFACE FINISH:	Matte	OPACITY:	95
BASE MATERIAL:	Fabric	GLOSS MEASUREMENT:	7 +/- 10% by angle of 60°
ADHESIVE MATERIAL:	Solvent Acrylic Removable	DURABILITY:	*Indoor: Up to 6 months depending on traffic. *Outdoor: Up to 3 months depending on traffic and weather.
LINER MATERIAL:	Double PE Coated Paper	STORAGE:	Up to six months if stored in proper conditions (cool, dry place 50-80°)
LINER WEIGHT:	140 GSM +/- 10%	ROLL LENGTH:	100 Ft.
LINER CALIPER:	6 Mil +/- 1	ROLL WIDTHS:	54"
FACE STOCK WEIGHT:	230 GSM +/- 10%	CORE:	3"
FACE STOCK CALIPER:	13 Mil +/- 1	PRINT SIDE:	Print Side Out
BRIGHTNESS:	92 (ISO Blue Whiteness)	INK RECOMMENDATIONS:	ECO-SOLVENT LATEX UV
WHITENESS:	109 (CIE Ganz)		

*Surface must be cleaned before installation, all loose debris removed from surface. For best results, apply with a rubber roller to ensure edges are sealed and water cannot get under graphic



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to six months if stored in proper conditions (cool, dry place 50-80°)